



EUCARAY® RC 400

D_{ca}

Small 1/4" size flexible radiating cable for applications up to 2.4GHz

Radiating Cables

Eupen EUCARAY® radiating cables have been developed to provide RF-coverage for wireless applications in confined areas. They provide homogeneous and continuous RF-coverage, and allow simultaneous transmission of multiple wireless services. EUCARAY® radiating cables are engineered and produced in Belgium to highest quality standards for best performance and longest lifetime.

Product Description

The EUCARAY® RC 400 is designed for installation in areas with reduced size. It can be used in train wagons, buildings, automation environments. Its very thin design features low weight and small bending radius.



Features and Benefits

- From 30 to 2700 MHz with resonant frequencies*
- Thin and flexible cable, with low bending radius
- Main Applications: Inbuilding, In-Train WLAN 2.4 GHz

Certification and Fire Behaviour

Halogen-free, Low-smoke and Flame-retardant outer jacket:

- Low corrosive gas emission acc. to IEC 60754-2
- Flame retardant acc. to IEC 60332-1-2 and IEC 60332-3-25
- Low smoke emission acc. to IEC 61034
- Reaction to fire according EN 50399 D_{ca} s2, d2, a1
- Compliant to EN 50575
- Fulfils the requirements of EN 45545-2:2013+A1:2015

Ordering Information

Ordering name: **RC 400-HLFR**

Recommended connectors and cable preparation tool:

- N Male: [NM50RC400](#)
- N Female: [NF50RC400](#)
- Tool: [SPTC50RC400](#)

^{*)} EUCARAY® achieves low coupling losses due to the patented slot design. Resonant frequencies are narrow-band VSWR peaks that usually occur in non-used bands of the radio-spectrum. Their amplitude generally decreases the higher the order.

More information under: www.radiating-cables.com

www.eupen.com



EUCARAY® RC 400

D_{ca}

Technical Information

• Size		1/4"
• Frequency range	MHz	30 - 2700
• Recommended Frequency bands		Inbuilding, In-Train WLAN 2.4 GHz
• Cable Type		RMC (Radiated Mode Cable)
• Material		Flame retardant polyolefin
• Slot design		Groups of slots at short intervals
• Impedance	Ω	50 +/- 2
• Velocity Ratio	%	85
• Capacitance	pF/m (pF/ft)	78 (23.8)
• Inner Conductor DC resistance	Ω/1000m (Ω/1000 ft)	4.30 (1.31)
• Outer Conductor DC resistance	Ω/1000m (Ω/1000 ft)	6.80 (2.07)
• Inner Conductor Material		Copper clad aluminium wire
• Dielectric Material		Cellular polyethylene
• Outer Conductor Material		Overlapping copper foil with slot groups, bonded to the jacket
• Diameter Inner Conductor	mm (in)	2.8 (0.111)
• Diameter Dielectric	mm (in)	7.3 (0.285)
• Diameter over Jacket	mm (in)	10.2 (0.402)
• Minimum Bending Radius, Single Bend	mm (in)	100 (3.94)
• Cable Weight	kg/m (lb/ft)	0.110 (0.074)
• Tensile Strength	daN (lbf)	27 (60)
• Indication of Slot Alignment		embossed line 180° opposite
• Storage Temperature	°C (°F)	-70 to +85 (-94 to +185)
• Installation Temperature	°C (°F)	-25 to +60 (-13 to +140)
• Operation Temperature	°C (°F)	-40 to +85 (-40 to +185)
• Longitudinal Loss and Coupling Loss ⁽¹⁾		

Frequency	Longitudinal Loss dB/100m (dB/100ft)	Coupling Loss	
		C50% (dB)	C95% (dB)
150 MHz	4.79 (1.46)	70	80
450 MHz	8.55 (2.61)	72	76
900 MHz	12.44 (3.79)	67	74
1800 MHz	18.37 (5.60)	63	69
2200 MHz	20.64 (6.29)	64	70
2400 MHz	21.72 (6.62)	61	66

• Resonant Frequencies	MHz	210;630;1050;1470;1890;2310 MHz
• Recommended Clamp Spacing	m (ft)	0.5 (1.64)
• Distance to Wall Recommended / Min.	mm (in)	80 - 180 (3.15 - 7.00) / 50 (1.96)

The above stated values are nominal values and subject to manufacturing tolerances as follows: Longitudinal Loss +/- 5 % and Coupling Loss +/- 5 dB.

As with any radiating cable, the performance in building or tunnel may deviate from figures measured according to the IEC 61196-4 standard.

¹⁾ Measured in tunnel according to **IEC 61196-4 - Ground Level Method**.

Distance = 2m. C50 & (C95) are the average coupling losses with 50% (95%) probability calculated in accordance with the standard.

Coupling loss measurements taken in accordance with IEC 61196-4 - Free Space Method are available on request.

All information on this datasheet is subject to change without notice.