

NB1800-LgWac-G

Industrial Router with LTE-APAC + WLAN-ac + 2x GbE + SFP + GNSS

High-performance and modular mobile router with Gigabit Ethernet and SFP port for use in industrial environment.



Keyfeatures

| | |
|------------------------------|--|
| Mobile / Cellular | 1x LTE, UMTS, GSM for APAC |
| SIM | 2x Micro SIM |
| WiFi / WLAN | 1x Dual-band IEEE 802.11 a/b/g/n/ac (Wi-Fi 5), 100 Clients in Access Point Mode |
| Ethernet | 2x Gigabit Ethernet, 1x SFP |
| Extended Storage | 1x SD Card |
| Serial / Fieldbus | 1x RS-232/485 |
| Positioning | Multi-GNSS |
| Operation Temperature | -40 °C to +70 °C |
| Software | Routing, Network Services, VPN, Firewall, Link Management, Supervisor, SDK, free updates |
| Compliance | CE (RED) |
| Modularity | Extensions on request |

Product description

The powerful NB1800 router enables fast Internet access in an industrial environment.

Applications

- Industrial Security
- Point of Sale
- Public WiFi
- Smart Grid
- Oil & Gas
- Renewable Energy
- Mining
- Factory Automation
- Smart Traffic
- CCTV

Specifications

| | | |
|--------------------------|--|---|
| Mobile / Cellular | Standard | 1x Multimode LTE, UMTS, GSM for APAC 4G - LTE B1 (2100), B3 (1800), B5 (850), B7 (2600), B8 (900), B28 (750) 3G - DC-HSPA+/UMTS B1 (2100), B2 (1900), B5 (850), B8 (900) 2G - GSM/GPRS/EDGE B2 (1900), B3 (1800), B5 (850), B8 (900) Category LTE Cat 4 Antenna ports 2x2 MIMO Data rate down / up (max) 150 Mbps / 50 Mbps Voice CSFB FCC ID XPYTOBYL280 |
| | Region Connectors SIM | Asia and Pacific (APAC) 2x SMA female 2x Micro SIM - 3FF |
| WiFi / WLAN | Standard | 1x WLAN 2.4/5 GHz a/b/g/n/ac (Wi-Fi 5) Wireless standard IEEE 802.11a/b/g/n/ac (Wi-Fi 5) Frequency 2.4/5 GHz Diversity 2x2 MIMO Data rate (max) 300 Mbps (2.4 GHz) / 866 Mbps (5 GHz) Modes Client or access point (up to 100 clients) FCC ID TK4WLE600VX |
| | Connector | 2x SMA female |

| | | |
|-------------------------|---------------------|---|
| Ethernet | Standard | 2x Gigabit Ethernet Ethernet standard 1000BASE-T, Auto MDIX Speed 10/100/1000 Mbps 1x SFP SFP standard Depending on module Speed 10/100/1000 Mbps |
| | Connector | 2x RJ45, 1x SFP cage (mini GBIC) |
| Positioning | Standard | 1x Multi-GNSS Receiver BeiDou, Galileo, GLONASS, GPS/QZSS 72-channel u-blox M8 engine 3 concurrent GNSS channels Antennas Active or passive Accuracy Up to 2.5 m CEP Sensitivity Up to -167 dBm Services Standalone, Assisted GPS Data server with JSON, NMEA data stream |
| | Connector | 1x SMA female |
| USB | Standard | 1x USB 2.0 Host |
| | Connector | 1x Type A |
| Serial, Fieldbus | Protocol | 1x RS-232/485 combo (software switchable) Protocol EIA-232 Signals TX, RX Signal level High > 5 VDC, low < -5 VDC Bit rate Up to 115 200 Bit/s Protocol EIA-485 Signals A, B Signal level Differential output voltage, loaded 1.5 VDC - 3.6 VDC Bit rate Up to 115 200 Bit/s Termination 120 Ω for RS-485 configurable by software |
| | Connector | 1x Terminal block header 3.5 mm (screw locking) |
| Extended Storage | | SD Card Slot type microSD Speed (read / write) 600 kByte / s Application Store user and logging data of SDK or LXC applications SD card not included |
| System | Core | 1.3 GHz dual-core, 1 GB RAM, 4 GB flash |
| | Module Slots | 2x miniPCIe (PCIe + USB), 2x Extension (USB) |
| Software | Features | NetModule Router Software (supported features depending on product variant) Package The standard software package includes an intuitive user interface, covering all modern routing protocols and enables efficient mass deployment. General Fail-safe update (FOTA), upgrade via USB, HTTP(S), (S)FTP or TFTP, remote CLI & WebGUI, RADIUS authentication, Simple Certificate Enrollment Protocol (SCEP), Hardware- und Software Watchdog Remote Management Manage and monitor devices with SNMP V1/V2/V3, Netmodule vendor MIB, telnet, SSH, or HTTP/HTTPS Cellular Networking Multi-SIM / eSIM support (optional license), multi-APN support, signal strength monitoring, dedicated bearers, CSFB/VoLTE calls (optional license) Wireless LAN Access Point, Client Mode, Mesh Point or Dual Modes (Mesh Access Point / Access Point - Client), WLAN Pseudo-Bridge Client Mode: Multiple Client SSID Profile, Encryption: Open, WEP, WPA1/2/3-Personal, WPA1/2/3-Enterprise. Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, Protected Management Frames (802.11w) AP Mode: Multi-SSIDs (up to 8) Encryption: Open WPA1/2/3-Personal, WPA1/2/3-Enterprise Fast Roaming: Fast BSS Transition (802.11r), PreAuthentication, DFS support Protected Management Frames (802.11w) Client Tracking, Band Steering, Hide SSID broadcasting, Isolate Clients, Accounting, Short guard Intervall Mesh Mode (802.11s): Encryption: None, SAE. Gateway announcements Link Management Link prioritization, link aggregation, load balancing, multipath-TCP, IP-passthrough, link supervision, Services DHCP Client/Server, DNS Caching Server, Email, SMS Service, NTP Client/Server, SNTP Server, DynDNS, SSH Server, SNMP Agent, HTTP/HTTPS/FTP Server, IPv6 for WAN, 802.1x over Ethernet, MQTT Broker Voice Gateway (SIP, Call Routing, Audio with optional license) Coovachilli Hotspot Routing Destination, policy, multipath, mobile-IP, OSPF, BGP, multicast, TCP-MSS clamping, bridging discovery protocols LLDP, CDP, SONMP, EDP, FDP, IRDP, VRRP, STP/RSTP, VRRP, VLAN, PPPoE, VXLAN VPN OpenVPN, IPsec (IKEv1 and IKEv2), PPTP, GRE, L2TP, CSD dial-in, Certificate revocation service Firewall Stateful firewall, connection tracking, NAT, NAPT, masquerading, bridge filtering, Adress translation (based on SRC and DST ports) Encryption supporting password protected PKCS12 files, integrated random certificate key generator, "Let's encrypt" certificate, ECC (Certificates with Elliptic Cryptography) Quality of Service Diffserv, SFQ, HTB, Priority-based Queuing, Netflow (Softflow) Programmability SDK Troubleshooting Logging, Ping, Traceroute, Tcpdump, Speed-test |
| | Licenses | GNSS Enabled service GNSS location service Server with JSON-, NMEA stream |

| | | |
|-----------------------|---------------------------------|---|
| Power | Input Voltage | 12, 24, 48 VDC Nominal voltages 12, 24, 48 VDC Absolute voltages 12 VDC to 48 VDC (-25 % / +10 %) |
| | Connector Consumption | 1x Terminal block header 3.5 mm (screw locking) 11 W (average), 20 W (max) |
| Mounting | | DIN-Rail |
| Dimensions | W x H x D | Width 61 mm x height 128/140 mm x depth 121 mm |
| Weight | | 800 g |
| Environment | Operating Temperature | -40°C to +70°C |
| | Ingress Protection Level | IP40 |
| MTBF | | 240'000 h / 27.4 years, according SN29500 at environmental temperature 40 °C |
| Certifications | Compliance | CE according to 2014/53/EU (RED), 2011/65/EU (RoHS) |
| | Domain | Industrial |
| Order Code | | NB1800-LgWac-G |